

Types of Standard and Customized Compounds

Color Concentrates

- Color concentrates are used for color-coded wire insulation, tubing, films and injection molded parts. Properties include superb surface finish, color consistency and dispersion - even at high extrusion rates.
- Our color concentrates are based on neat resin and pigment only, where the raw materials are highly scrutinized for specifications and compatibility.
- Standard colors available include White, Orange, Blue, Green, Brown, Red, Black, Yellow, Violet and Gray. Custom colors are available upon request.
- We incorporate strict QC procedures to ensure consistent pellet size and integrity, giving you optimized production and consistency lot to lot without adjustments.

Cross-Linkable Compounds

- Cross-link compounds are used for insulating air frame, industrial and shipboard wiring. These compounds are also used where high temperature, abrasion and cut-through resistance are important considerations. They are manufactured as ready-to-use products and may be pigmented.
- Typical customization of products includes color, melt flow rate of final compound, and amount of cross-linking needed for the application. The processed article can be cross-linked using electron-beam radiation or gamma radiation.

Foam Concentrates

- Foam concentrates are designed for gas injection foaming used for manufacture of LAN and coaxial cable. Two types of standard grades are available: higher flow FEP foam concentrates for thin wall applications (LAN) and lower flow for thicker wall constructions (coaxial). We can also customize foam concentrates to meet your application parameters.
- The properties of foamed insulation help minimize signal loss, enhance high-speed data transmission, and save weight and material, potentially resulting in a cost savings to you.

Conductive/Anti-Static Compounds

- Made with ETFE or PFA and carbon, conductive compounds are used for control of heat and static electricity. Wire coated with a conductive fluoropolymer may be used to wrap and thaw frozen pipes, to locate pipelines leaks by detecting thermal change, or as static dissipative fuel lines.
- Conductive compounds are manufactured as ready-to-use products. Typical customization of products includes melt flow rate of final compound and conductivity needed for the application. Consistency and processability are the key factors in developing these compounds.

Types of Standard and Customized Compounds

Flexible AR Compounds

- Flexible AR compounds are based on modified ETFE and a proprietary fluoroelastomer where many of the desirable properties of ETFE are maintained but in a more flexible form.
- These materials are ideal for applications such as wire and cable (automotive, industrial, aerospace, transit and appliance markets), films and sheets, tubing and pipe, and electronic components.
- The heat resistance of flexible AR compounds can be enhanced by radiation curing and can be cross-linked without the presence of curing agents or coagents.

Reinforced Compounds

- Reinforced compounds incorporate glass fibers, carbon fibers or mineral fillers for enhanced dimensional stability, toughness, abrasion resistance, shrinkage resistance and thermal conductivity characteristics.

Lubricated Compounds

- Lubricated compounds contain lubricious fillers such as FEP or PTFE for applications requiring low-friction, abrasion-resistant surfaces or linings, such as push-pull cable for vehicle brakes.

Adhesive Compounds

- Adhesive compounds are modified ETFE used in applications where strong adhesion to polyamide polymers, especially nylon 12, is required. These compounds also exhibit high permeation resistance to many fluids and gases, especially automotive fuels.

**AGC Chemicals Company
AGC Inc.**

Shin-Marunouchi Bldg.,
1-5-1 Marunouchi
Chiyoda-ku, Tokyo, 100-8405 Japan
Tel: +81-3-3218-5438
www.agc-chemicals.com

AGC Asia Pacific Pte., Ltd.

460 Alexandra Road, #32-01
PSA Bldg., Singapore, 119963
Tel: +65-6273-5656
www.agc-asiapacific.com

**AGC Chemicals Trading
(Shanghai) Co., Ltd.**

Room 4008/09, 40F, T1
Raffles City Changning
No. 1133 Changning Road
Shanghai, China 200051
Tel: +86-21-6386-2211
www.agcsh.com

**AGC Chemicals
(Thailand) Co., Ltd.**

24th Floor, Bangkok Insurance Bldg
25 South Sathorn Road
Kwang Tungmahamek Khet Sathorn
Bangkok 10120, Thailand
Tel: +66-2-679-1600
www.acth.co.th

AGC Chemicals Europe, Ltd.

PO Box 4, York House
Hillhouse International
Thornton, Cleveleys
Lancashire FY5 4QD, UK
Tel: +44-(0)-1253-209-600
www.agcce.com

**AGC Chemicals Europe, Ltd.
Commercial Centre**

World Trade Center, Zuidplein 80
1077 XV Amsterdam, Netherlands
Tel: +31-(0)-20-880-41-70
www.agcce.com

AGC Chemicals RUS

Russian Federation, 121596
Moscow, Gorbunova Street 2,
Grand Setun Plaza, Bldg. 204, BC
5th Floor, Block B, Office B 504
Tel: +7-918-555-34-37
www.agcce.com

AGC Vidros do Brasil Ltda.

Al. Ministro Rocha Azevedo, 38,
10º andar, cj 1004
Cerqueira César
São Paulo, SP, Brasil
CEP 01400-000
Tel: +88-11-3373-9981
www.agcchem.com



**Chemistry
for a Blue Planet**
AGC Chemicals

AGC

AGC Chemicals Americas, Inc.

55 E. Uwchlan Avenue, Suite 201
Exton, PA 19341
United States of America

Telephone: +1 610-423-4300
Toll Free (US only): 800-424-7833
Fax: +1 610-423-4305

www.agcchem.com

Visit our website for compliance information and industry certifications.

The information provided herein is related only to the specific product designated and may not be applicable where such product is used in combination with any other materials or in any process.

NO REPRESENTATION OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE, ARE MADE HEREUNDER.

The user of this product has the sole responsibility to determine the suitability of the product for any use and manner of use intended. This document may be revised after its issuance, and the user is advised to use the latest revision.