

EXCESTAR™

Silane Modified Polyether



EXCESTAR™ is a family of moisture curable silane terminated polyether polymers used in construction sealants and elastic adhesives offering high elongation with low viscosity.

Typical Properties of EXCESTAR™

Product	Polymer Structure	Molecular Weight	Viscosity (mPa-s at 25°C)	Characteristics
EXCESTAR™ S2410E	Linear	17,000	11,000 - 20,000	Low Modulus, High Elongation
EXCESTAR™ S2420E	Linear	17,000	12,000 - 23,000	Medium Modulus
EXCESTAR™ S888E	Linear	23,000	17,000 - 28,000	Medium Modulus, High Elongation
EXCESTAR™ S6250E	Branched	15,000	2,500 - 4,900	High Modulus, Low Viscosity
EXCESTAR™ S3430E	Branched	17,000	6,000 - 13,000	High Modulus, Low Viscosity
EXCESTAR™ S3630E	Branched	20,000	14,000 - 22,000	High Modulus, Good Elongation

- Grades listed above are those marketed and sold in the US. Other grades are available upon request.
- pH range is 5 – 10; Density is ~1.0 g/cm³ at 25°C

* Note: The values shown above are typical values, not guaranteed values

* AGC reserves the right to revise its product range at any time without prior notice

Performance Advantages

- Environmentally friendly / Safe
- Long-lasting elasticity
- Good adhesion, weatherability and paintability
- Non-staining

AGC Chemicals Americas, Inc.
55 E. Uwchlan Avenue, Suite 201
Exton, PA 19341
United States of America

Telephone: +1 610-423-4300
Toll Free (US only): 800-424-7833
Fax: +1 610-423-4305

www.agcchem.com

Visit our website for compliance information and industry certifications. EXCESTAR™ is a trademark of AGC Inc.

